

RD125LC





RD125LC SPECIFICATIONS

ENGINE

Type	2-stroke, liquid-cooled, Torque Induction, single
Displacement	123 cc
Bore and stroke	56.0 × 50.0 mm
Compression ratio	6.4:1
Max. power (DIN)	12.2 PS (9.0 kW) @7,500 rpm
Max. torque (DIN)	1.2 kg-m (11.9 Nm) @7,000 rpm
Lubrication	Autolube
Carburation	VM24SS
Ignition	CDI
Starter system	Kick
Fuel tank capacity	13.0 l
Oil capacity	1.1 l
Transmission	6-speed
Final transmission	Chain drive

CHASSIS

Overall length	1,940 mm
Overall width	695 mm
Overall height	1,140 mm
Seat height	755 mm
Wheelbase	1,275 mm
Ground clearance	165 mm
Dry weight	98 kg

Suspension

Front	Telescopic forks
Rear	Monocross suspension

Brakes

Front	Hydraulic disc
Rear	Drum

Tyres

Front	80/100-16-45PR
Rear	90/90-18-51PR

*Specifications and appearance of Yamaha motorcycles shown here may vary according to requirements and conditions and are subject to change without notice.
For further details, please contact your Yamaha dealer.
Always wear a helmet and eye protection.*

Mitsui Machinery Sales (U.K.) Ltd.
Oakcroft Road
CHESSINGTON/SURREY KT9 1SA
Tel: 01-3975111
Tlx: 929929

 **YAMAHA**
MC-RD125LC-87 UK